

CARE SHEET FOR YOUR SHUTTERS

Operating The Blades

- Clearview: Use both hands to operate the blades/louvres (open and close). The clearview strip is not to be used to operate the blades/louvres
- Centre Tiltrod: Use the Tiltrod Bar to operate the blades/louvres (open and close)

Operating The Panels

- For By-Pass/Sliding Shutters:

Ensure all blades/louvres are closed before operating sliding panels to avoid blades from hitting each other (clash of blades on front & back panels)

- For Bi-Fold Shutters:

Ensure all blades/louvres are closed before operating bi-fold panels to avoid blades from hitting each other when stacking the panels (clash of blades on joint panels)

Care For The Shutters

- Blades/Louvres should be opened and closed regularly
- All panels on Bi-fold shutters should be stacked regularly
- All panels on Sliding shutters should be slided regularly
- Shutters should be cleaned regularly to prevent build up of dirt and dusts
 - ✓ Use the vacuum with a soft brush attachment to lightly vacuum the blades/louvres. Microfibre or static cling duster can also be used as an alternative
 - ✓ Tilt down all the blades/louvres and vacuum/clean in a downward stroke
 - ✓ Do not push too hard against the blades/louvres to avoid scratching the blades/louvres
 - ✓ Do one side first before vacuuming/cleaning the other side
 - ✓ Use a soft damp cloth to remove any stubborn dirt/dusts

CARE SHEET FOR YOUR SHUTTERS

If you use soft damp cloth to clean the shutter, please ensure you use a dry soft cloth to fully dry the shutter

- ✓ For Timber Shutters, use dry soft cloth or microfibre or static cling duster only.
 - ✓ Vacuum or sweep away dirt/dusts that may have fallen to the floor or tracks
 - ✓ It is important not to use cleaning solutions or abrasive cleaners on shutters that may damage the shutter surfaces
- External Aluminium Shutters should be hosed down regularly and washed with a very mild detergent to remove contaminants from airborne dirt and salt in coastal areas. Please ensure to rinse off thoroughly and remove any excess water with a cloth.

Please use the following table as a guideline to clean your external Aluminium Shutters:

ENVIRONMENT	DESCRIPTION	FREQUENCY
Mild	10km from coastal / suburban areas	Every 6 months
Moderate	5km from coastal / high traffic areas	Every 3 months
Severe	1km from coastal / heavy industrial areas	Every 2 weeks
Highly Severe	500m from coastal / heavy industrial areas	Every 1 week